PA and Lighting		
Mixing panel	pc	1
Amplifier XP1000	pc	1
Rotating searchlight	pc	2
Microphone db Tehnologies PU860	pc	2
Cancer tripod	pc	1
DVD reciever	pc	1
Speaker Stand	pc	2
LED Spot Par 56	pc	4
Moving head	pc	1
Photocells set	pc	3
Cables and Connectors	pc	1
Security Equipment		
Metal safe	pc	1
Metal detector - hand	pc	1
Metal detector - framed	pc	1
Safe with 10 units	pc	1
Equipment "John Huxley "		
Table A/RBlack Jack	pc	4
Table A/R large roulette	pc	2
Pocker Boxes	pc	60
Plastic Jumbo Index Brown	pc	300
Plastic Jumbo Index Green	pc	300
Cutting Cards Plastic Red	pc	100
Cutting Cards Plastic Black	pc	100
Wheelchecks Ymbol Non Decal Custom	pc	3360
Chips Hotstamped 39mm Plain Rim-Yellow	pc	600
Chips Hotstamped 39mm Plain Rim-Blue	pc	600
Cash Box Sec 2LK Comp	pc	2
Slot Cover Cash Brass	pc	3
Shoe 6 PK Black ACR JH LOGO	pc	4
Discard Holder 6 Pack Brass	pc	4
Tip Box STD 1LK SLD 15 cm Max	pc	4
Slot Cover Tip Brass	pc	4
Chips 39 mm 2Col STD Decal -Green	pc	1100
Chips 39 mm 2Col STD Decal -Light Gray	pc	600
Chips 43 mm 3Col STD Decal -White	pc	100
Chips 43 mm 3Col STD Decal -White	pc	100

Chips 39 mm Col STD Decal	pc	3000
Bar casino		
Bar board - stoned	pc	7
Sinks	pc	3
Bar board - stoned	pc	1
Bar racks	pc	1
DVD	pc	1
Computer equipment		
SERVERS		
Cpu Server Quad- Core XeonX3220 2,4GHz (1066MHz, 8MB, Kentsfield, 100W, S775) box MB Server Socket -755 INTEL i300 (ATX, FSB 1066Mhz, 4DDR II SDR, VGA, GbitLAN, Serial ATA II/300-RAID) S3000AH Kingston DDR-II1024MB PC667 HDDDesktop Hitachi GST Deskstar P7K500 320 GB 7200RPM 16MB cache Serial ATA II- 300 FDD 1,44MB RAID PROMISE FastTrack TX4310 Serial ATA II-300 PCI 4 ch (JBOD, 10, 5, 0, 1), 5-pack Intel Extreme Graphics 2 (intagrated) Intel Gigabit LAN Port (intagrated) Mainboard supported, 7 slots, PSU installed internal 550W, Black LG DVD+RW 16X, Dual Layer	pc	1
CASE: Chieftec CH-01B-B-SL-550W, Midi Tower Mesh Serries, 550W Real Power Supply (with 1pc. USB/Firewire/Audio) for ATX & EATX, 6X Hard Drives MAINBOARD: Supermicro X7DVL-E Dual Xeon, 667/1066/1333MHz FSB, Intel 5000V Chipset, Up to 16 GB 1 pc. DDR2 667 & 533 (FB-Dimm), 6xSATA 3.0 Gbps, RAIDO. 1, 5, 10 support, 2xPCI-Express, 2x PCI-X Intel dual port gigabit LAN, IPMI support, VGA; CPU Intel Xeon e5410 2,33 ghZ 12m cACHE, 1333FSB, Quad core, RAM:2XGB DDR2-667 FB-DIMM LP FMHS PB-FREE (Intel AMB); HDD: 4x Western Digital HDD 320 GB SATAII RAID EDITION RE2-7200rpm 8,9ms 16 MB cache; DVD_RW/+RW LG, Dula Layer, IDE, Black; SCSI CONTR. LSI SAS controller - 8704ELP, LSliBBU005 - LSI Battery for 8708/8704/8888 RAID	pc	1
SOFTWARE		
Windows 2003 Server Std R2A 1-4CPU 5clt	pc	2
MS Windows Server CAL, 2003 OLP NL AE, Device	pc	25
WORK STATION - Shuffler		
Core 2 Duo E2220/ 2.4G/1M/BOX, INTEL D945GCNL/945G/BULK, 1GB DDR2 800 KINGSTON 160GB HITACHI 7K 160/SATA2/8M, FOXCINN 3GTLA-001/420W PFC, Delux Kbd, DKM-326 optical mouse, 17 LCD LG L1718S/5MS/BLACK-SLV, OEM Windows Vista Business 32bit and MS Office 2007 Basic Edition	pc	1
WORK STATION - Registration desk		

Core 2 Duo E2220/ 2.4G/1M/BOX, INTEL D945GCNL/945G/BULK, 1GB DDR2 800 KINGSTON 160GB HITACHI 7K 160/SATA2/8M, FOXCINN 3GTLA-	pc	1
001/420W PFC, Delux Kbd, DKM-326 optical mouse, 19 LCD LG L1918S/5MS/BLACK-SLV, OEM Windows Vista Business 32bit and MS Office 2007 Basic Edition		
WORK STATION - Operational Manager		
Core 2 Duo E2220/ 2.4G/1M/BOX, INTEL D945GCNL/945G/BULK, 1GB DDR2 800 KINGSTON 160GB HITACHI 7K 160/SATA2/8M, FOXCINN 3GTLA-001/420W PFC, Delux Kbd, DKM-326 optical mouse, 19 LCD LG L1918S/5MS, OEM Windows Vista Business 32bit and MS Office 2007 Basic Edition	pc	1
WORK STATION - General Manager		
Core 2 Duo E2220/ 2.4G/1M/BOX, INTEL D945GCNL/945G/BULK, 1GB DDR2 800 KINGSTON 160GB HITACHI 7K 160/SATA2/8M, FOXCINN 3GTLA-001/420W PFC, Delux Kbd, DKM-326 optical mouse, 22 WIDE LG L22WS/2,5/3K:1 SVR 19 LCD LG L1918S/5MS, OEM Windows Vista Business 32bit and MS Office 2007 Basic Edition	pc	1
Other technical equipment		
Printer - Hp Color Laser Jet CP 1515n	pc	1
Printer - HP LaserJet P1006	pc	1
Card Printer –Zebra P330i - High speed printing - 144 cards/hour for color, single side (YMCKO) - 600 cards/hour for resin black (K) - Windows® Drivers: 2000, XP, Server 2003; Vista compatible	pc	1
Magnetic card encoder (HICO/LOCO)	pc	4
Online web camera	pc	1
Switch - HP ProCurve Switch 1700-24	pc	1
CKR -22U 68 - 19" RACK 22U 600X800	pc	1
RA0-MS-A01 - Complete set of screw, washer and nut	pc	20
Dome waterproof color camera with infrared illumination, Sharp 1 / 4 "Super, 420 TVLine, 1 Lux / F1.2, IR on 0 lux, AES, AGC, AWB, 12 VDC 250 mA, 25 IR LED, to 15 m, hand Choir. spin-360, vertical 120, From -10 0S ~ +50 0S with obektiv3, 6 millimeters		

# Casino technical equipment **DG216T-000CNV DynaColor 16Channel DVR 480ips REAL TIME Record CD-RW VGA USB 2.0 NAS 2Ch Audio CMS Support** • Dual-Main Output • MPEG-4 high quality compression, 5-10 times smaller than MJPEG • Triplex operation enabling simultaneously view live or playback while continuing to record • Remote monitoring, recording, playback, change system settings and dome camera control via Ethernet and/or Internet • Built with ezBum Thl technology, two keys(Search/Call) are all you need for completing the video export • By selecting ezRecord Thl function, user can select the period of days to record instead of complicated record settings • Support VGA main output • Live display: 480pps (NTSC)/400pps (PAL) • Recording Rate: 480pps (NTSC)/400pps (PAL) • 2 Channels, in & out, for audio recording • Support up to intemal 4 HDD / 1 Optical drive + 3 HDD • Gigabit Ethernet for dedicated NAS device, DynaStorage ThI 200 • Mesh network support(IEEE 802.11 bIg) • Built-in CD-RW or DVD+RW for video clip exporting (optional) • USB2.0 port for video clip exporting, support USB thumb drive, extemal CD-RW and DVD+RW • Easy software upgrade via Network, USB ThumbDrive, or CD-RW	pc	1
D7313 Series CCTV Control Keyboard • Remote control via RS-485 interface • 3-axis joystick control of PTZ • Can control up to 255 devices • Firmware upgrade via RS-232 port • Built-in clock for date and time recording • Supports Pelco D, Pelco P, and DSCP protocols • Password protection and key-lock function	pc	1

DynaHawk™ 701/801+ S1/S2 Series Integrated High Speed Dome Camera **Precise and Accurate Dome Camera Performance** • High Resolution 540 TV lines • Preset speed up to 400°/sec. • Preset accuracy of 0.225°• 360° Endless Pan • Proportional Pan & Tilt Speed • Preset Position / Auto-Pan / Sequence / Cruise • Auto-Calibration • Digital / Mechanical Image Flip (180°) **Dynamic Dome Camera Applications** • Multi-language OSD • Schedule function • Multiple built-in protocols • 16 privacy masks • 8 alarm inputs, 1 alarm output • Motion Detection • Flexible indoor / outdoor mountings • Compact lightweight design for easy installation • Weatherproof housing • Integrated Pelco Coaxitron® support • Integrated BOSCH Biphase® support **Superior Camera Image Quality** • Minimum illumination 0.01 Lux (B/W) • Digital Slow Shutter • Electronic Shutter • Auto White Balance • Backlight Compensation • Auto Exposure • Image Inverse • Removable IR Cut Filter • Wide Dynamic Range (WDR); optional • 2D/3D Noise Reduction **Optional Network Functions** • H.264 and MJPEG compression • D1 Real-time resolution • 3D de-interlaced support	pc	6
DE200 - Audio and Video Edit • MPEG-4 high quality compression • 16 channels video input • Triplex+ operation enabling simultaneous viewing live or playback while continuing to record • Embedded Linux operating system • Real-time "live display" for each channel • Recording frame rate up to 480 pps (NTSC) / 400pps (PAL) • 2 Channels of audio recording/playback • Three USB2.0 ports for vido clip export and/or backup • Easy software upgrade via USB ThumbDrive®, DVD+RW, or Internet • Remote Application • Up to 4 internal hard disk drives support up to 1TB capacity • Hard disk drive full alarm for noticing • 2X Digital Zoom available in live mode • Export video (AVI & DRV) with audio and digital Signature • Exported AVI file can be played in any PC with DivX decoder installed • Automatic camera detection (Plug & Play) • Covert camera operation provides enhanced security and administrator Control • Per camera configuration for camera settings, frame rate, picture bit rate, alarms, motion detection • Programmable day/night/weekend scheduling • Programmable main monitor/call-monitor switching sequence • Dual vido out for monitoring • Powerful alarm processor allows flexible alarm trigger	pc	1

and responses, including alarm, motion, and camera failure • Text Message (Short Message Service; SMS) sent to your mobile phone for alarm notice • Dome control protocols: DynaColor, Pelco D, Pelco P, AD422 and Fastrax 2 • Pre-program the OSD menu using a mouse connected to the USB port		
D77H06 Stand for Integrated High Speed Dome Camera Modification - **701/801+ S1/S2**	pc	6
DG Audio – 16 extender for **DG216T-000CNV DynaColor 16Channel DVR 480ips REAL TIME**	pc	1
CS-Fujinon vari-focal lens 2.8-8mm, F 0.95, aspheric, automatic blind, DC regulated, 1/3 format, CS mount - Unparalleled brightness at the maximum aperture of F0.95, optimizing the performance at low lightning intensity - Vari focal lens f=2.8-8mm, can be used on 1/3 or on 1/4 cameras - Wide 2.9mm, achieving the horizontal field angle of 94 degree (when used on 1/3 cameras) ® - High accuracy aspherical lens adopted, achieving the quality image - Built-in Neutral Density Filter -ND Filter-, supporting high sensitivity cameras - Compact and lightweight design	pc	1
VISION – LCD screen- 19 inch LCD colored screen, resolution 1280x1024, PAL/NTSC, 16,2 M colors, Brightness 450cd, contrast 700:1, 2 composite ports 750OVp-p, 1 S-VIDEO, 1-YPBPR, 1-VGA, 3 AUDIOPORTS	pc	1
Color camera in fire alarm - Modification YK-2611A - Sony 1/3 Super HAD CCD sesor, 380 TVLine, 0,4 Lux/F2, AES, AGC, AWB, 12VDC/220mA with Cone lens 3,7 mm, alum. Corpus	pc	1
Mini dome camera - Modification YK-2C54 - Sony 1/3 Super HAD CCD sesor, 380 TVLine, 0,4 Lux/F2, AES, AGC, AWB, 12VDC/220mA with Cone lens 3,7 mm, alum. Corpus	pc	2
Sound board - Modification YK-8312 - 12vdc	pc	5
Dome waterproof color camera with infrared illumination, Sharp 1 / 4 "Super, 420 TVLine, 1 Lux / F1.2, IR on 0 lux, AES, AGC, AWB, 12 VDC 250 mA, 25 IR LED, to 15 m, hand Choir. spin-360, vertical 120, From -10 0S ~ +50 0S with obektiv3, 6 millimeters	pc	6
Plastic stand for camera modofication- YK-206	pc	1
Power unit 24 VAC/3,0 A, corpus -Modification STD-3024S	pc	6
Power unit 12 VAC/3,0 A, corpus -Modification STD-3013S	pc	9
BNC connectors for crimping	pc	36